


## STANDARD FEATURES

- 2 year Warranty
- 24V class 2 control circuit with 40VA transformer to protect against short circuit
- On board receiver with antenna
- External radio control terminal strip
- Low friction powder metal limit cam nuts with fully adjustable rotary type limit switch assembly
- Three button open-close-stop control station Nema-1
- Continuous duty industrial motor with external reset overload protection (1-phase) or external thermal overload relay motor protection (3-phase)
- Motor removable without affecting limit settings
- Heavy duty worm gear reduction in oil bath gearbox
- 1-1/4" or 1-3/8" cast iron flanged bearings on gearbox final output shaft
- Rigid steel wall mounting frame around gearbox
- 1.5 second time delay on all open functions standard on 1.5, 2 & 3 HP
- Solenoid brake standard
- #50 roller chain and sprockets on final drive
- Emergency chain hoist with electrical cut-out switch for manual operation
- Chain keeper
- Universal left or right hand mounting
- Baked on dark grey coat finish
- Shipping weight 125 lbs
- N-1 Micanan photocells included for doors up to 24' wide




---

**When ordering a PRO-GHC operator, supply the following information:**

---

- Door height
  - Door width
  - Type of door
  - Horsepower
  - Voltage/ Phase
  - Safety devices
  - Door shaft diameter & door shaft key size
  - Mounting (LH or RH, Bracket or Wall mount)
  - Control circuit options (see page 5-6)
- 

