



STANDARD FEATURES

- 2 year Warranty
- 24V class 2 control circuit with 40VA transformer to protect against short circuit
- On board receiver with antenna
- External radio control terminal strip
- Low friction powder metal limit cam nuts with fully adjustable rotary type limit switch assembly
- Three button open-close-stop control station Nema-1
- Continuous duty industrial motor with overload protection
- Motor removable without affecting limit settings
- Heavy duty 5LV-belt
- #41 roller chain & sprockets on all internal drives
- Adjustable friction clutch
- Mechanical brake system
- Solenoid brake (optional PRO-JB) recommended for large doors
- #50 roller chain and sprockets on final drive
- 3/4" permanently lubricated & sealed precision ball bearings on pulley shaft
- 1" permanently lubricated & sealed ball bearings on final drive shaft
- Emergency disconnect with electrical cut-out switch for manual operation
- Chain keeper
- Left or right hand mounting
- Baked on dark grey coat finish
- Shipping weight 95 lbs
- N-1 Micanan photocells included for doors up to 24' wide




When ordering a PRO-j operator, supply the following information:

- Door height
 - Door width
 - Type of door
 - Horsepower
 - Voltage/ Phase
 - Safety devices
 - Door shaft diameter & door shaft key size
 - Mounting (LH or RH, Bracket or Wall mount)
 - Control circuit options (see page 5-6)
-



WALL MOUNT



BRACKET MOUNT

