

RBH

HOIST OPERATOR WITH ROLLER BEARINGS AND BRAKE



Logic 5.0 The Next Generation of Commercial Door Operators

Hoist (RBH) style commercial door operators are optimal for industrial applications. RBH-style operators include a floor level chain hoist to ease manual operation in an emergency or power outage. The operators are typically mounted to the wall when used with larger sectional overhead doors with vertical or high lift and mounted to the wall or the front of the hood when used with rolling doors and grilles. RBH operators are attached to the door jackshaft to indirectly drive the door.

Connectivity

- **MyQ® Technology** enables you to securely monitor and control your facility operator and lights with your smartphone, tablet or computer for greater peace of mind.
- **Alerts** can be received as email or pop-up (push) notifications on a mobile device, ensuring the status of your commercial door.
- **MyQ Mobile App** is a free download with no annual activation fee.

Safety and Security

- **Security+ 2.0®** safeguards your facility – with every click, a new code is sent to the commercial door operator so the door opens only for you.

UL 325 requires all commercial door operators to be either constant pressure to close or be equipped with a primary external monitored entrapment protection device.

LiftMaster® is the leading brand of professionally installed commercial door operators and access control products for businesses worldwide. We are committed to quality products, innovative designs and comprehensive services which exceed our Customers' expectations.

LiftMaster®

ELITE SERIES®

For more information visit www.devancocanada.com

Devanco Canada Accessories:



O/C/S 8-Door Transmitter (8L5-OCS)

Compatible with all Liftmaster® Logic 5.0 commercial operators. Also works with the LiftMaster® 850LM and 860LM receivers to control O/C/S on 8 doors.



LED Stop & Go Traffic Light (YSG12-24LED)

Provides a bright visual indication that the door is completely open. Reduces the chance of accidents and injuries. Ideal for fire stations, parking garages and loading docks. 10-32V AC/DC or 120VAC input voltage. Black housing also available. LiftMaster® TLS1 Card recommended.

MyQ Accessories:



Internet Gateway (828LM)

Enables owners of commercial door operators to connect their operators to the Internet to monitor, control and receive alerts regarding status of each door.



Door and Gate Monitor (829LM)

Enables monitoring and closing within a facility of up to four commercial doors.



Remote Light Control (825LM)

Operates a plug-in light using a commercial door operator remote control, or the LiftMaster Internet Gateway using your smartphone or computer.

Entrapment Protection Devices:



Monitored Dual-Sided Photo Eyes (CPS-OPEN4)

Provides primary entrapment protection on doors up to 45ft wide. NEMA 4X rated.



Monitored Optical Edge System (OES)

Thru-beam infrared optical sensors, premium rubber door edge that can be cut to length for exact fit.

Additional Accessories:



3-Button Remote Control (813LM)

Provides Security+ 2.0™ Technology and compatible with multiple radio technologies. Includes OPEN, CLOSE and STOP functionality, and green/yellow/red color bars.

STANDARD FEATURES:

DUAL VOLTAGE CONNECTIONS

Increase flexibility by enabling the installer to select the required voltage, within phase, to meet job-site requirements.

Within phases, voltage is selectable at the time of installation with the placement of a connector.

- Single-Phase: 115V and 230V
- Three-Phase: 208V, 230V and 460V
- 575V is a discrete model without field-selectable voltage

FLOOR LEVEL CHAIN HOIST WITH ELECTRICAL INTERLOCK

Provides easy disconnect and manual operation in an emergency.

ROLLER BEARINGS

Heavy-duty, grease filled industrial pillow block bearings on a 1 in. output and reduction shafts for increased durability.

CONTROL FUNCTION SELECTOR DIAL

Enables easy selection and programming of (7) wiring types, from constant pressure to close, to specialized Timer-to-Close functionality to meet end-user needs.

TIMER-TO-CLOSE

Conveniently and confidently closes the commercial door automatically after a predetermined amount of time has elapsed for added security and peace of mind.

CONTINUOUS-DUTY HIGH-STARTING TORQUE MOTOR

Performs in demanding industrial overhead and rolling door applications.

MOTOR REMOVABLE WITHOUT AFFECTING LIMIT SWITCH SETTINGS

Saves time and money for maintenance.

ADJUSTABLE FRICTION CLUTCH

Helps to protect door and operator from damage should the door meet an obstruction.

MID-STOP

Enables partial opening of door to a preprogrammed position for energy savings, time savings, and convenience.

MAXIMUM RUN TIMER

Reverses or stops door if closing time exceeds expected time-frame to limit damage to door and operator.

DELAY-ON-REVERSE CIRCUIT

Prevents abrupt reversal of door, reducing wear on the door and operator system.

3-BUTTON CONTROL STATION WITH MAINTENANCE ALERT SYSTEM (MAS)

Provides OPEN/CLOSE/STOP functions and notification when routine maintenance is required.

SPECIFICATIONS:

SECURITY+ 2.0® RADIO RECEIVER

Standard on-board with Logic 5.0 operators. Accepts up to (90) single-button or (30) 3-button remote controls plus up to (30) wireless keypads or an unlimited number of DIP switch remotes.

MOTOR

Continuous-duty high-starting torque motor with instant reverse and overload protection. Available in 1/2, 3/4 and 1 HP; single- or three-phase. Capacitor start on single-phase. Removable without affecting limit switch settings.

For more information, please visit
www.devancocanada.com or call toll free at 855-931-3334

WIRING TYPE

Operators are factory preset to C2 wiring, providing momentary contact to open and stop, with constant contact to close. Monitored entrapment protection, using approved photo sensors or sensing edges is optional, although recommended, when using C2, D1 or E2. All other wiring types, B2, T, TS and FSTS can be selected with the addition of an appropriately monitored entrapment protection device (LiftMaster® CPS-U photo eyes, LiftMaster OES monitored sensing edge, or a monitored sensing edge supported by the CPS-EI, as examples). Logic 5.0 operators can only accept UL-Approved LiftMaster monitored entrapment protection devices.

CONTROL CIRCUIT

5V DC NEC Class 2.

DRIVE REDUCTION

First-stage heavy-duty 5L V-belt; second-third-fourth stages #48 chain; #50 output sprocket chain.

BRAKE

Standard on all RBH operators.


CONSTRUCTION

NEMA 1 type electrical box, heavy-duty 11-gauge steel frame with durable powder coat finish, all reduction sprockets drilled and pinned to shafts.

WARRANTY

Two Years.

TECHNICAL INFORMATION:



		MAXIMUM DOOR AREA (SQ. FT.)					
ROLLING	24 ga. Steel	22 ga. Steel	—	20 ga. 18 ga. Steel	16 ga. Steel	—	
	Aluminum Grilles	Aluminum Doors	—	Steel Grilles	—	—	
SECTIONAL	—	24 ga. 22 ga. Steel	20 ga. Steel	—	16 ga. Steel	—	
	Fiberglass	Aluminum Doors	Wood Doors	—	—	—	
	—	—	24 ga. Steel Insulated	—	20 ga. Steel Insulated	16 ga. Steel Insulated	
HP	1/2	400	350	320	280	250	200
	3/4	560	500	450	380	325	250
	1	640	625	580	475	400	310

NOTE: On steel insulated doors, a 24-gauge back panel is assumed. If a heavier back panel is supplied, use the next higher HP rating. Recommended Duty Cycles: Up to 25 per hour, up to 80-90 per day.