




ATRIUM is an easy-to-use and powerful 10 door access control system. ATRIUM's embedded web server enables you to add, delete or modify users/cards, user access privileges, holidays and schedules. Instantly lock/unlock doors, view system status and events from anywhere in the world using a web browser, smart phone or tablet. No need to purchase or download an app! ATRIUM's embedded web server does all this for free.



Performance Merging with Simplicity




Card Readers and Keypads




Proximity Cards and Tags




Inputs (10 onboard zone inputs, 20 with zone doubling)



Door Locks (2 door locks, 750mA @ 12Vdc output)




AC22 2-Door Controller



Readers




Tamper Switch (N.C. Contact)




Alarm Sounder




Battery 12V, 7AH (UL/LULC: YUASA WNP7-12 recommended, Europe: CDVI 87AH recommended)



Expander Module Local Bus (RS485) The expander module Local Bus supports an overall distance of 1220m (4000 ft.). Daisy chain, star or "Y" configurations (or a combination of these) are supported.



10-Door Access Control System



Main Features	ATRIUM 10 Door System
Embedded Web Server	✓
Pre-assembled universal power supply (120V / 240V)	✓
Expander module auto-detection	✓
FREE ATRIUM software	✓
Users / Cards	1,000 / 1,000
Areas	10
Inputs	50 (100 using zone doubling)
Schedules / Periods	100 Schedules. Each schedule supports 100 time periods.
Access Levels	100
Event Buffer	1,000



Card Enrollment Mode in Four Quick & Easy Steps

With today's ever-increasing hectic pace, time is becoming more and more precious. ATRIUM's quick and easy Card Enrollment Mode makes adding or deleting cards faster than ever before. So easy in fact that a computer is no longer required to accomplish these common tasks. You will definitely appreciate this highly effective and speedy feature.

With the addition of each new card (or tag) using the quick and easy card enrollment mode, a user will be created automatically in the ATRIUM system. Personalize the user information using the free ATRIUM software or via the embedded web interface using a browser, smart phone or tablet. No need to download an App!



1. Present the "MASTER CARD" to a reader & open the door. A door position switch (door contact) is required.
2. Within unlock time, present the "PROGRAMMING CARD" to the same reader. LEDs will flash in sequence, 2 Red flashes + 2 Green, to indicate programming mode is activated.
3. Present cards or tags, one by one, to the reader.
 - NEW cards will be ADDED. - Green LED will flash and a pulsed beep will be emitted.
 - EXISTING cards will be DELETED. - Red LED will flash and a long beep will be emitted.
4. Present the "PROGRAMMING CARD" again to stop enrollment mode. You are done.

The "MASTER CARD" and "PROGRAMMING CARD" are provided with the ATRIUM system.



Performance Merging with Simplicity



AC22 | 2-Door Controller

- Control 2 doors / 2 readers (up to 10 doors with four AX22 2-door expanders)
- Embedded Web Server
- Pre-assembled universal power supply (120V / 240V)
- Free ATRIUM software
- On-board RS-485 expansion communication bus
- Expansion module auto-detect technology
- Quick and easy card enrollment procedure
- 10 Inputs (20 using zone doubling technology)
- Totally fuseless system
- Includes metal cabinet with cabinet door lock, cabinet door and wall tamper switches
- Bell output (12Vdc @ 3A max., 40W)
- 2 Lock outputs: 750mA @ 12Vdc each (configurable as dry contact relays)
- 2 additional onboard dry contact relays (form C) 5A @ 250Vac, 7A @ 125Vac, 7A @ 30Vdc
- Ultra-fast firmware update (less than 10 seconds)
- Wiegand & ABA Track II magnetic stripe compatible
- Maintenance-friendly snap on terminal connectors
- Comprehensive LED status indicators
- Environment: -22°C to 50°C (-4°F to 122°F)



AX22 | 2-Door Expander

- Control 2 doors / 2 readers
- 1220m (4000ft.) 4 conductor RS-485 expansion bus (No jumpers or DIP switches)
- 2 Lock outputs: 750mA @ 12Vdc each (configurable as dry contact relays)
- 2 additional onboard dry contact relays (form C) 5A @ 250Vac, 7A @ 125Vac, 7A @ 30Vdc
- Includes metal cabinet with cabinet door lock, cabinet door and wall tamper switches
- Wiegand & ABA Track II magnetic stripe compatible
- 10 Inputs (20 using zone doubling technology)
- Comprehensive LED status indicators
- Environment: -22°C to 50°C (-4°F to 122°F)

ATRIUM KITS

- AC22KITB | Controller Kit
 - 1 x AC22
 - 2 x NANO (black mini proximity readers)
- AX22KITB | Expander Kit
 - 1 x AX22
 - 2 x NANO (black mini proximity readers)

ATRIUM kits are also available with mullion (STAR) or single-gang (SOLAR) stylish proximity readers, in black or white.