

PASSPORT™ STAND-ALONE PROXIMITY CARD READER

PPLX



DOES YOUR BUSINESS NEED A MORE SECURE METHOD OF ACCESS CONTROL?

Card access has been out of reach for most owners of small to medium sized businesses. The cost of technology is prohibitive and up to this point has been designed for large government, commercial and industrial users.

The LiftMaster® Stand-Alone Proximity Card Reader (Model PPLX) offers high-end access control and security in a simple stand-alone format. This system allows for up to 50,000 user proximity cards or keyfobs in minutes. Also, the PPLX allows for simple deletion of lost or stolen cards without the need to re-program the entire user set. Rugged and durable, the PPLX is sealed in a weatherproof (IP67) enclosure and can be easily mounted to any flat interior/exterior surface, or installed in any single gang electrical enclosure.

For convenience, a handheld radio programming unit (Model PPRP) eliminates the need to bring a laptop computer to program the stand-alone unit.

For more information:
www.devancocanada.com
or call toll free at 855-931-3334



Model PPRP

Hand-held programmer for use with LiftMaster® model PPLX, Stand Alone Proximity Access Control Device.

LiftMaster®

SECURITY. SIMPLICITY. FLEXIBILITY. WE BRING IT ALL TOGETHER.

Advanced technology means far greater simplicity. LiftMaster® security access products are easy to use, work together seamlessly and are adaptable to a variety of applications – residential and commercial.

The ideal combination of perimeter control devices - and very easy to live with. Delivering just what you would expect from access technology... and from Chamberlain.

STANDARD FEATURES

- 6" Read Range**
- 50,000 User Capacity**
- Programmable Output Relay**
(NO/NC)
- Multiple Wiegand Protocol**
(Sentex®, 26 Bit Industry Standard, Passport™)
- "Latch Mode" to Hold the Door or Gate Open**
- Timed Anti-Passback Logic**
- Programmable as Stand-Alone or Wiegand Pass-through**
- Simple to use Hand-Held Radio Programmer**
(Model PPRP)

SPECIFICATIONS

Power Requirements

5-14 VDC, 150mA (max load)

Outputs

SPST Solid State Relay. 1A max. @60 VAC or DC
Normally open or normally closed (field programmable)

Inputs

Default is Remote Open (requires contact closure).
Also programmable as Bicolor (Red or Green) LED Control or Buzzer/LED control for online systems (see Operating Guide).

Wiegand Output

Any Wiegand Format up to 40 bits
Maximum Distance: 500 ft. - 5 or 6 conductor 20 gauge shielded cable

Environment

Access Control Unit and Cards
Ambient Temp. -40° to +70°C (-40° to +158°F)
Humidity 0 to 95% (non-condensing)

AVAILABLE CONFIGURATIONS

Model Number	Description
Components:	
PPLX	Stand Alone Proximity Reader (No Power Supply - No Programmer - No Cards)
PPRP	Proximity Radio Programmer (Only)
PS12D2A	Power Supply 12Vdc 2.0A (Only)
PPCSC	Proximity Card (Clamshell) (Shipped in sleeves of 50)
Kits:	
PPRO	Includes (1) Reader and (1) Power Supply
PPRKO	Includes (1) Reader, (1) Power Supply and (1) Programmer
PPRK100	Includes (1) Reader, (1) Power Supply, (1) Programmer and (100) Cards
PPRK250	Includes (1) Reader, (1) Power Supply, (1) Programmer and (250) Cards

LiftMaster®



For more information:
www.devancocanada.com
 or call toll free at 855-931-3334